



Spock 1 NEW



Designed by FLOS Outdoor, 2013




LED source included. Integrated electrical power supply 220-240V ON/OFF. Fixing bracket included. Equipped with a 1000 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Optional IP68 connectors available. The metal nail for ground installation needs to be ordered separately. Optional accessories to regulate the light beam. Dimmable version available upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

\//hita



Main specifications

EAN	8054793686400
Mounting	Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	9
System power (W)	11
Source flux (lm)	1124
Lumen Output (lm)	811

Physical

Colodi	VVIIICE
Orientation	Adjustable
Longitudinal tilting (°)	270
Net weight (kg)	0.89
Package height (mm)	150
Package width (mm)	135
Package length (mm)	180
IP internal	66

Download

Mounting instructions

₹ ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D ₹ ZIP **↓** ZIP











https://professional.flos.com/en/global/product/spock-1-fa54100201/

FA54100201

Schematic light drawing



Bean	n Angle:	19°
h(m)	E(lx)	D(m)
1	3816	0.34
2	954	0.68
3	424	1.01
4	239	1.35
5	153	1.69

30°॒	7 31	316 c	d M	30°;
Lum	inous	flux	lumi	naire
811 h	m			

311 lm			

Beam angle C0-180 (°)

Extreme cut off

Electrical Photometric

Symmetric

4000 80

20

No

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance Dimmable version on request

Accessories & Power Supply





FA20830

Flood Diffuser Spock 1



OPTIONAL Accessory

FA20630

Visor Spock 2



OPTIONAL Accessory

FA203

Kit Ground Spikes Spock 1/Spock 2/Spock 3



OPTIONAL Accessory

FA2113

Anti-Glare Louvre Spock 1



OPTIONAL Accessory

FA26130

Elliptical Lens Spock 1



OPTIONAL Accessory

F990F00A000

S.P.D. (SURGE PROTECTION DEVICE)



OPTIONAL Accessory

F990C01000C

3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)



OPTIONAL Accessory

F990C00A000

2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)