

# FLOS

03.2232.14A Black

**Spot** NEW

Designed by FLOS Architectural, 2020



LED - Power LED - 6W - 369lm - 4000K - CRI> 90 - Beam° 13

Accent lighting LED module to be installed in The Micro Running Magnet System.  
Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

## Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	6
System power (W)	6
Source flux (lm)	625
System flux (lm)	369
Efficacy (lm/W)	61.5

## Physical

Color	Black
Orientation	Adjustable
Rotation (°)	267
Longitudinal tilting (°)	90
Length (in)	1.62
Net weight (lb)	0.16
IP internal	20



## Download

[Family spec sheet](#) [ZIP](#)

[Mounting instructions](#) [PDF](#)

## Photometric Files

[LDT / IES](#) [ZIP](#)

## Technical Drawings

[2D](#) [ZIP](#)


[3D](#) [ZIP](#)



## Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

## Schematic light drawing



### Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	13
Beam angle C90-270 (°)	13
UGR <sub>L</sub>	<10

### Electrical

Insulation class	III
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)