

# FLOS

03.2233.14A Black

**Spot** NEW

Designed by FLOS Architectural, 2020



LED - Power LED - 6W - 384lm - 5000K - CRI> 90 - Beam° 13

Accent lighting LED module to be installed in The Micro Running Magnet System.  
Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

## Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	6
System power (W)	6
Source flux (lm)	665
System flux (lm)	384
Efficacy (lm/W)	64

## Physical

Color	Black
Orientation	Adjustable
Rotation (°)	267
Longitudinal tilting (°)	90
Length (in)	1.62
Net weight (lb)	0.16
IP internal	20



## Download

[Family spec sheet](#) ZIP

[Mounting instructions](#) PDF

## Photometric Files

[LDT / IES](#) ZIP

## Technical Drawings

[2D](#) ZIP


[3D](#) ZIP



## Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

## Schematic light drawing



Beam Angle: 13°

h(m)	E(lx)	D(m)
1	6386	0.23
2	1597	0.45
3	710	0.68
4	399	0.90
5	255	1.13

Luminous flux Luminaire  
384 lm

### Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	5000
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	13
Beam angle C90-270 (°)	13
UGR <sub>L</sub>	<10

### Electrical

Insulation class	III
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)