

FLOS

03.6286.14BDA Black

Spot 120 Dali Version


Designed by FLOS Architectural, 2016



Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|-------------------|---------------------|
| Mounting | Track |
| Environment | Indoor dry location |
| Light source type | LED |
| LED type | Power LED |
| Lamp category | LED |
| Bulb finish | Clear |
| Number of heads | 1 |
| Power (W) | 14 |
| System power (W) | 14.5 |
| Source flux (lm) | 1003 |
| System flux (lm) | 458 |
| Efficacy (lm/W) | 31 |

Physical

| | |
|--------------------------|------------|
| Colour | Black |
| Orientation | Adjustable |
| Rotation (°) | 360 |
| Longitudinal tilting (°) | 90 |
| Transversal tilting (°) | 90 |
| Length (mm) | 46 |
| Net weight (kg) | 0.35 |
| Package height (cm) | 19 |
| Package width (cm) | 22 |
| Package length (cm) | 17 |
| IP internal | 20 |

Download

[Mounting instructions](#) PDF

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP


[Bim](#) ZIP




Schematic light drawing



Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

| | |
|--------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| LED Life / Failure Ratio | L80B50 |
| Beam angle C0-180 (°) | 31 |
| UGR _L | 9 |

Electrical

| | |
|---------------------|---------------------------------------|
| Insulation class | III |
| Main voltage (Vac) | 24 |
| Forward voltage (V) | 24 |
| Driver | Remote excluded |
| Dimmable | Yes |
| Dimming type | Dimmable DALI 2 |
| Dimming range (%) | 1-100 |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |

Notes

Maximum 11 spots for a single driver. Accessories included (honeycomb and screening crosspiece). For wireless lighting control, choose integrated Casambi versions.