



Spot 150 Casambi integrated

Designed by FLOS Architectural, 2020



Accent lighting LED module.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Hack
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	22.5
System power (W)	24.1
Source flux (lm)	2569
Lumen Output (lm)	1937
Efficacy (Im/W)	96.37

Physical

vvriite
No
Adjustable
360
90
57
0.42
20



*installed in The Tracking Magnet

Download

Mounting instructions

₩ PDF

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D	<u>↓</u> ZIP
3D	⊥ ZIP
₿Bim	<u>↓</u> ZIP

















https://professional.flos.com/en/global/product/spot-150-casambi-integrated-03.8073.40acb/

03.8073.40ACB

Schematic light drawing



Beam Angle:		21	
h(r	n) E	(lx)	D(m
1	119	75	0.37
2	29	94	0.74
3	13	31	1.1
4	7	48	1.48
-	- 1	70	1 Ω

Luminous flux luminaire 1937 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	21
Beam angle C90-270 (°)	21
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	470
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable Casambi
Dimming range (%)	10-100
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

Accessories & Power Supply









OPTIONAL Accessory

Optical

08.0526.00

Snoot shielding cone

OPTIONAL Accessory

Optical

08.8428.00

Honeycomb

OPTIONAL Accessory

Optical

08.8429.00

Screening crosspiece

OPTIONAL Accessory

Optical

08.8431.0

Elliptical lens







OPTIONAL Accessory

Optical

08 8432 00

Flood lens

OPTIONAL Accessory

Optical

08 0526 40

Snoot shielding cone

OPTIONAL Accessory

Optical

18 0526 RW

Snoot shielding cone