

# FLOS

03.6302.14B Black

## Spot Module On Board Dimmer

Designed by FLOS Architectural, 2016



Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	yes
LED type	Power LED
Lamp category	LED
Ilcos	No
Bulb finish	Clear
Number of lamps	1
Power (W)	8
System power (W)	8.4
Lumen Output (lm)	418
Efficacy (lm/W)	49.76

### Physical

Colour	Black
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	34
Length (mm)	34
Net weight (kg)	0.19
IP internal	20
IP external	20



### Download

Mounting instructions [Download PDF](#)

Item information [Download JPG](#)

### Photometric Files

LDT / IES [Download ZIP](#)

### Technical Drawings


2D [Download ZIP](#)

3D [Download ZIP](#)

Bim [Download ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14
Extreme cut off	No
UGR <sub>L</sub>	<16

Electrical

Insulation class	III
Main voltage (Vac)	24
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmer on board
Dimming range (%)	20-100

Notes

Maximum 21 spots for a single driver. For wireless lighting control, choose integrated Casambi versions.

Accessories & Power Supply



OPTIONAL  
Accessory  
Optical

08.8427.14  
Screening external ring for  
Running Magnet spot module



OPTIONAL  
Accessory  
Optical

08.8759.00  
Elliptical lens



OPTIONAL  
Accessory  
Optical

08.8760.00  
Frosted Medium lens



OPTIONAL  
Accessory  
Optical

08.8761.00  
Frosted Flood lens