


# FLOS

03.9510.EU Brushed Rose Gold

## Super Line Down NEW

Designed by FLOS Architectural



LED luminaire for general lighting with a signature minimalist and compact design, to be installed on ceilings by means of suspension. Power source included in installation kits must be ordered separately.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	38.6
System power (W)	39
Source flux (lm)	4609
Lumen Output (lm)	3571
Efficacy (lm/W)	91.56

### Physical

Colour	Brushed Rose Gold
Orientation	Fixed
Length (mm)	1500
Net weight (kg)	1.45
IP internal	20
IP external	20



### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)



[Bim](#) [↓ ZIP](#)



Schematic light drawing



Ecodesign and Energy  
Labelling



Replaceable (LED only)  
light source by a  
professional

Replaceable control  
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50 - 50.0000h (Tc 85°C)
Beam angle C0-180 (°)	76
Beam angle C90-270 (°)	82
Extreme cut off	No

Electrical


Insulation class	III
Forward voltage (V)	35.9
LED current (mA)	1050
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

Cable 5 m

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Accessories & Power Supply




REQUIRED  
Accessory

Installation

08.9076.40

Interconnection Accessory




REQUIRED  
Accessory

Installation

08.9076.02

Interconnection Accessory




REQUIRED  
Accessory

Installation

08.9076.14

Interconnection Accessory




REQUIRED  
Accessory

Installation

08.9076.ET

Interconnection Accessory



REQUIRED  
Accessory

Installation

08.9076.EU

Interconnection Accessory



REQUIRED  
Power supply

Electrical

08.0524.02

Remote Power Supply Kit 60W.  
Non Dimmable



REQUIRED  
Power supply

Electrical

08.0524.14

Remote Power Supply Kit 60W.  
Non Dimmable



REQUIRED  
Power supply

Electrical

08.0524.40

Remote Power Supply Kit 60W.  
Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0524.ET


Remote Power Supply Kit 60W.  
Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0524.EU


Remote Power Supply Kit 60W.  
Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0520.02A


Surface Kit 60W. Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0520.14A


Surface Kit 60W. Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0520.40A


Surface Kit 60W. Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0520.ETA


Surface Kit 60W. Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0520.EUA


Surface Kit 60W. Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0522.02A


Recessed Kit 60W. Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0522.14A


Recessed Kit 60W. Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0522.40A


Recessed Kit 60W. Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0522.ETA


Recessed Kit 60W. Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0522.EUA


Recessed Kit 60W. Non Dimmable



REQUIRED  
Power supply  
Electrical

08.0521.EUA


Surface Kit 60W. Dali Version



REQUIRED  
Power supply  
Electrical

08.0521.ETA


Surface Kit 60W. Dali Version



REQUIRED  
Power supply  
Electrical

08.0521.40A


Surface Kit 60W. Dali Version



REQUIRED  
Power supply  
Electrical

08.0521.14A

Surface Kit 60W. Dali Version



REQUIRED  
Power supply  
Electrical

08.0521.02A


Surface Kit 60W. Dali Version



REQUIRED  
Power supply  
Electrical

08.0523.EUA


Recessed Kit 60W. Dali Version



REQUIRED  
Power supply  
Electrical

08.0523.ETA


Recessed Kit 60W. Dali Version



REQUIRED  
Power supply  
Electrical

08.0523.40A


Recessed Kit 60W. Dali Version



REQUIRED  
Power supply  
Electrical

08.0523.14A

Recessed Kit 60W. Dali Version



REQUIRED  
Power supply  
Electrical

08.0523.02A

Recessed Kit 60W. Dali Version



REQUIRED  
Power supply  
Electrical

08.0525.02A

Remote Power Supply Kit 60W.  
Dali Version



REQUIRED  
Power supply  
Electrical

08.0525.14A

Remote Power Supply Kit 60W.  
Dali Version



REQUIRED  
Power supply  
Electrical

08.0525.40A

Remote Power Supply Kit 60W.  
Dali Version



REQUIRED  
Power supply  
Electrical

08.0525.ETA

Remote Power Supply Kit 60W.  
Dali Version



REQUIRED  
Power supply  
Electrical

08.0525.EUA

Remote Power Supply Kit 60W.  
Dali Version