



Superloon

Designed by Jasper Morrison, 2015



48W - 2716lm - 2200-2800K

Adjustable floor lamp providing direct light. Painted or chrome-plated aluminium body with metal spinning head, die-cast joints and extruded stem. Silk screened PMMA diffuser. Edge Lighting technology light source. Optical switch sensor placed on the stem that provide Warm Tone dimming function. Power cord length 250 cm. Plug-in power supply with interchangeable plugs.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Floor
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	48
System flux (lm)	2716

Physical

Colour	Chrome
Length (mm)	754
Cord colour	Black
Net weight (kg)	11
Package volume (m3)	0.11
IP internal	20



Download

业 PDF
↓ PDF
⊥ PDF

Photometric Files

LDT / IES



Technical Drawings

2D	₹ ZIP
3D	业 ZIP



















https://professional.flos.com/en/global/product/superloon-f6630057/

F6630057

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2200-2800
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/48
LED voltage Vf (Vdc)	null
Power Supply	Remote included
Dimmable	Yes
Power Supply Type	Electronic 48V
Dimming interface	Dimmer Integrated
Plug type	Type G, Type A, Type C
Ratteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D




Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts



O0. Assembly Coaxial Connector RF3390130
O1. Chrome diffuser F6632057
O2. Mobile legs RF25119
O4. Black plug assembly kit & 48V RF6600130
driver

DOWNLOAD







RF3390130

Assembly Coaxial Connector

F6632057

Chrome diffuser

RF25119

Mobile legs

RE6600130

Black plug assembly kit & 48V driver