


SuperWire S3

Designed by Formafantasma, 2025

90W - 6450lm - 2700K - CRI> 90



SuperWire is the first family of modular lamps designed by Formafantasma for Flos. A magical and poetic project, with an essential design but a great stage presence, which recalls the work of the great glass masters of the last century. Made of planar glass and polished aluminum, its design originated from the development of a custom-made light source that emits a warm and homogeneous light. Made up of one or more hexagons of planar glass connected by a polished aluminum element, SuperWire lights up its entire surface thanks to a new source: a very thin, flat, soft, flexible LED strip measuring up to one meter, which emits a warm and homogeneous light along its entire length and which can be easily removed for replacement and repair, unique in the panorama of LED bulb-less lamps. Suspension models feature a concealed downlight module for functional accent lighting on tables, complemented by the warm, diffuse glow of the vertical modules.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

| | |
|------------------------|---------------------|
| EAN | 8059607075616 |
| Mounting | Suspension |
| Environments | Indoor dry location |
| Light Source Type | LED |
| Light sources included | Yes |
| LED type | Filament LED |
| Power (W) | 90 |
| System flux (lm) | 6450 |

Physical

| | |
|-----------------------------|----------|
| Color | Steel |
| Length (in) | 11.61 |
| Cord length (in) | 118.110 |
| Canopy length/diameter (in) | 8.504 |
| Canopy width (in) | 216 |
| Canopy height (in) | 1.850 |
| Net weight (lb) | 48.5 |
| Package volume (in) | 19833.28 |
| IP internal | 20 |

Download

Mounting instructions [Download PDF](#)

Photometric Files

ULD [Download ULD](#)

Technical Drawings

2D [Download ZIP](#)
3D [Download ZIP](#)



Photometric


| | |
|--------------------|------------|
| Lighting type | Total |
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| Extreme cut off | No |

Electrical


| | |
|--------------------|-------------------|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 100-240 |
| Driver | Remote included |
| Dimmable | Yes |
| Dimming type | Dimmable |
| Dimming interface | Dimmer Integrated |
| Batteries inside | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by an end-user



Replaceable control gear by an end-user



00. Led dimmer kit RF35452



RF35452

Led dimmer kit