

Suspension Glass Downlight 110 White Rod 100 mm Dali Version


Designed by Vincent Van Duysen, 2017



Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	13.5
System power (W)	14
Source flux (lm)	1371
System flux (lm)	309
Efficacy (lm/W)	22.07

Physical

Color	Red Glass
Trim	No
Orientation	Fixed
Length (in)	8.07
IP internal	20
IP external	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF


Photometric Files

LDT / IES	ZIP
-----------	---------------------

Technical Drawings

2D	ZIP
3D	ZIP

Schematic light drawing



Ecodesign and Energy
Labelling

Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
LED Life / Failure Ratio	L80B50 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	42
Beam angle C90-270 (°)	42
UGR _L	<16

Electrical

Insulation class	III
Forward voltage (V)	48
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency type	No

Notes

Only compatible with DALI profile version.