

# FLOS



03.8140.14ADA Black/Gold

## Suspension Panel 600 Rod 100 mm Dali Version

UPGRADE


Designed by Vincent Van Duysen, 2017



Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	40
System power (W)	40

### Physical

Colour	Black/Gold
Trim	No
Orientation	Fixed
Length (mm)	605
Net weight (kg)	4.96
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)

### Schematic light drawing



Beam Angle: 113°

h(m)	E(lx)	D(m)
1	539	3.05
2	135	6.09
3	60	9.14
4	34	12.19
5	22	15.24

Luminous flux luminaire  
1550 lm

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	113
Beam angle C90-270 (°)	113
Extreme cut off	No

## Electrical

Insulation class	III
Forward voltage (V)	48
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)

## Ecodesign and Energy

### Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

## Notes

Only compatible with DALI profile version.