

Suspension Panel 600 Rod 400 mm Dimmable 1-10V

UPGRADE

Designed by Vincent Van Duysen, 2017



Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 24.5                |
| System power (W)       | 25.6                |
| Source flux (lm)       | 3332                |
| System flux (lm)       | 1595                |

### Physical

|             |            |
|-------------|------------|
| Color       | Black/Gold |
| Trim        | No         |
| Orientation | Fixed      |
| Length (in) | 23.82      |
| IP internal | 20         |



### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |


### Photometric Files

|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |

Schematic light drawing



Photometric

|                          |                             |
|--------------------------|-----------------------------|
| Lighting type            | Direct                      |
| Light distribution       | Symmetric                   |
| CCT (K)                  | 2700                        |
| CRI>                     | 90                          |
| LED Life / Failure Ratio | L80B50>50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 113                         |
| Beam angle C90-270 (°)   | 113                         |

Electrical

|                     |                                          |
|---------------------|------------------------------------------|
| Insulation class    | III                                      |
| Forward voltage (V) | 48                                       |
| Driver              | Remote excluded                          |
| Dimmable            | Yes                                      |
| Dimming type        | Dimmable 1-10V                           |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not Included) |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **G**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Only compatible with 1-10V profile version.