

Suspension Panel 600 Rod 400 mm On Board Dimmer

40W - 1573lm - 3000K - CRI> 90 - Beam° 114

Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Power (W)	40
Source flux (lm)	3381
System flux (lm)	1573

Physical

Color	Black
Orientation	Fixed
Length (in)	1
Net weight (lb)	11.38
Package volume (in)	7628
IP internal	20




Download

Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)

Photometric Files

LDT / IES [ZIP](#)

Schematic light drawing



Beam Angle: 113°

h(m)	E(lx)	D(m)
1	572	3.05
2	143	6.09
3	64	9.14
4	36	12.19
5	23	15.24

Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	114
Beam angle C90-270 (°)	114

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	850
Driver	Remote