

06.2611.14.90 Black

## T Connector Feed Dimmable

Designed by FLOS Architectural, 2023

NEW



Ceiling surface, Wall surface

T-shaped connector. Can be powered via connections on the back. Rear feeding cable entry.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

Mounting	Ceiling surface, Wall surface
Environments	Indoor dry location
Light sources included	No

### Physical

Color	Black
IP internal	20



### Download

Family spec sheet	ZIP
Mounting instructions	PDF



### Photometric

Extreme cut off	No
-----------------	----

### Electrical

Insulation class	III
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)



Accessories & Power Supply



REQUIRED  
Power supply


Electrical

LEDSB60W24V-NDM-D01  
LED Driver, 24VDC, 60W, Non-Dimming, 120-277V



REQUIRED  
Power supply


LEDSB96W24V-NDM-D01  
LED Driver, 24VDC, 96W, Non-Dimming, 120-277V



OPTIONAL  
Power supply

Electrical


08.0613.14A  
Dimmable control box 1-10V, 24/48V. For remote installation.



OPTIONAL  
Component

Installation

06.2618.40A  
Track Cover 3000mm



OPTIONAL  
Component

Installation

06.2618.14A  
Track Cover 3000mm



OPTIONAL  
Connector

Electrical

06.2608.14  
Straight Connector



OPTIONAL  
Connector

Electrical

06.2608.40  
Straight Connector