FLOS

F7440000 Polished Aluminium

Taraxacum 88 Suspension 2

Designed by Achille Castiglioni, 1988




Halogen - 120 x 28W

Suspension fixture providing direct and reflected lighting. Structure formed by 20 pressed, polished aluminum triangles. 120 clear Globolux lamps housed around the structure. Steel ceiling fitting and rose.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607023570
Mounting	Suspension
Enviroment	Indoor dry location
Light source type	Bulb
Lamp category	Halogen
Lamp holder	E27
Ilcos	HSGSG
Number of heads	120
Power (W)	28

Physical

Colour	Polished Aluminium
Cord length (mm)	6000
Net weight (kg)	13.9
Package height (cm)	97
Package width (cm)	88
Package length (cm)	87
IP	20
IP external	20

RETILAP | IP 20 | IK 00 | IP 20

Download

Mounting instructions	PDF
Compatible dimmers	PDF
Spare Parts	PDF

Photometric Files

LDT / IES	LDT


Technical Drawings

2D	ZIP
3D	ZIP

©2022 Flos - P.IVA 00290820174 - 7/27/2022

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Luminous flux luminaire
26400 lm

The above drawing is for illustrative purposes only and refers to product code: F7440000WTARAXACUM_S2_120X25W-INC

Photometric

Lighting type	Total
Light distribution	Asymmetric


Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
Cord length (mm)	6000
Batteries inside	No
Charging min time	No

©2022 Flos - P.IVA 00290820174 - 7/27/2022

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.


Bulbs



NOT INCLUDED

RF24894

LED Globol Lamp 3W 200lm E27
180-265V 2500K



NOT INCLUDED

RF27119

LED Global Lamp E27 3W 2500K
Dimmable (Set 15pcs)

©2022 Flos - P.IVA 00290820174 - 7/27/2022

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.