



The Fast Track Surface Profile

Designed by FLOS Architectural, 2017




Length: 1500 - Ceiling surface

Electro-mechanical profile for surface installations in plasterboard ceilings, with 1m to 3m lengths. Not suitable for suspended installations. Power and interconnection cables must be ordered separately. Covers must be ordered separately. Fixed ceiling kit included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location

Physical

Colour	Black
Trim	No
Length (mm)	1500
Net weight (kg)	4.2











Electrical

Forward voltage (V)	48
Power supply	Remote excluded
Emergency	No

https://professional.flos.com/en/global/product/the-fast-track-surface-profile-06.1861.14/

06.1861.14

Accessories & Power Supply





Electrical

60.8919

LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac



REQUIRED
Power supply

Electrical

60.9170

LED power supply source for remote installation, 48V/120W. 220/240 Vac



REQUIRED
Power supply

Electrical

60.9607

LED power supply source for remote installation, 110Vac-150W / 220Vac-200W



REQUIRED Component

06.0303.00

Power feed cable



REQUIRED Component

08.9071.14

The Fast Track Surface Profiles End Caps. 2 unit kit



REQUIRED Component

08.9071.40

The Fast Track Surface Profiles End Caps. 2 unit kit



OPTIONAL Component

06.0301.00

Connection cable. Electrical and data connection



OPTIONAL Component

08.9074.14

The Fast Track Recessed-Surface Stopper





OPTIONAL

Electrical

06 1987 14

Multifunction Smart Device for Running Magnet & Fast Track

OPTIONAL

Electrical

06 1987 40

Multifunction Smart Device for Running Magnet & Fast Track