

## The Running Magnet Recessed Intermediate Profile


Designed by FLOS Architectural, 2015



'Electromechanical profile for recessed installation in plasterboard ceilings and walls. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

Mounting	Wall recessed, Ceiling recessed
Environments	Indoor dry location
Light sources included	no

### Physical

Colour	Black
Trim	No
Recessed depth (mm)	86
Length (mm)	1000
Net weight (kg)	2.80
IP internal	20
IP external	20

### Download

Mounting instructions

ZIP



### Electrical

Forward voltage (V) 24

## Notes

The Recessed version can only be installed on 12.5 mm thick plasterboard surfaces. Covers included with the power feed profiles. 90° corners available in the same plane (symmetrical element for left and right corners), symmetrical 90° inner and outer corners in different planes. Permanent or adjustable fastening kits available (optional). The fastening kits for the roof permit installing without using aluminium fastening profiles. Recommended for installations where the Running Magnet 2.0 cannot be installed before the suspended plasterboard ceiling (use 2 units).

---

Accessories & Power Supply



OPTIONAL  
Installation

08.8865.14A  
Endcap. 2 unit kit



OPTIONAL  
Installation

08.8866.14  
Fixed ceiling kit. 2 unit kit



OPTIONAL  
Installation

08.8867.14  
Adjustable ceiling kit. 2 unit kit



OPTIONAL  
Electrical

06.1987.14  
Multifunction Smart Device for  
Running Magnet & Fast Track



OPTIONAL  
Electrical

06.1987.40  
Multifunction Smart Device for  
Running Magnet & Fast Track