

## The Running Magnet Surface Feed Unit Profile


Designed by FLOS Architectural, 2015



Electromechanical profile for surface-mounting. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling surface, Wall surface
Environments	Indoor dry location
Light sources included	no

### Physical

Colour	Black
Trim	No
Length (mm)	1500
Net weight (kg)	4.65
IP internal	20
IP external	20

### Download

Mounting instructions

[ZIP](#)



### Electrical

Forward voltage (V)	24
Power supply	Remote excluded
Power supply type	Non Dimmable, Dimmable DALI 2, Dimmable Casambi

## Notes

Covers included with the power feed profiles. Attachment accessories included with all products.

90° corners available in the same plane (symmetrical element for left and right corner) and 90° symmetrical internal corners in a different plane, for the Surface and Down versions. For connection to the driver.

The inner part of the profile is always supplied in black.

---

Accessories & Power Supply



REQUIRED  
Power supply  
Electrical

60.9352  
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.



REQUIRED  
Power supply  
Electrical

60.9089  
Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W



REQUIRED  
Power supply  
Electrical

60.9407  
Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W



REQUIRED  
Installation

08.8887.14A  
Endcap. 2 unit kit



OPTIONAL  
Control interface  
Electrical

60.9678A  
LED module Dali/Push dimmable control unit for 12, 24 or 48Vdc



OPTIONAL  
Electrical

06.1987.14  
Multifunction Smart Device for Running Magnet & Fast Track