

## The Running Magnet Surface Intermediate Profile


Designed by FLOS Architectural, 2015



Electromechanical profile for surface-mounting. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                               |
|------------------------|-------------------------------|
| Mounting               | Ceiling surface, Wall surface |
| Environments           | Indoor dry location           |
| Light sources included | no                            |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | White |
| Trim            | No    |
| Length (mm)     | 2500  |
| Net weight (kg) | 6.50  |
| IP internal     | 20    |
| IP external     | 20    |

### Download

[Mounting instructions](#)

[ZIP](#)



### Electrical

Forward voltage (V) 24

## Notes

Covers included with the power feed profiles. Attachment accessories included with all products.

90° corners available in the same plane (symmetrical element for left and right corner) and 90° symmetrical internal corners in a different plane, for the Surface and Down versions.

The inner part of the profile is always supplied in black.

---

Accessories & Power Supply



OPTIONAL

Installation

08.8887.14A

Endcap. 2 unit kit



OPTIONAL

Electrical

06.1987.40

Multifunction Smart Device for  
Running Magnet & Fast Track