

The Running Magnet Suspension Down Feed Unit Profile

Designed by FLOS Architectural



Length: 78.74 - Suspension

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Suspension
Power (W)	100

Physical

Color	White
Length (in)	78.74
Net weight (lb)	12.35
Package volume (in)	3601
IP internal	20



Download

Family spec sheet	ZIP
Mounting instructions	PDF



Electrical

Insulation class	II
Forward voltage (V)	24
Driver	Remote

Accessories & Power Supply



REQUIRED
Power supply
Electrical


LEDSB60W24V-NDM-D01
LED Driver, 24VDC, 60W, Non-Dimming, 120-277V



REQUIRED
Power supply
LEDSB96W24V-NDM-D01
LED Driver, 24VDC, 96W, Non-Dimming, 120-277V



REQUIRED
Power supply
Electrical
LEDSB30W24V-NDM-D01
LED Driver, 24VDC, 30W, Non-Dimming, 120-277V




REQUIRED
Electrical
08.8886.40
Surface power supply for direct and indirect lighting with housing for the driver



REQUIRED
Installation
08.8887.40A

Endcap. 2 unit kit




OPTIONAL
Power supply
Electrical
08.0613.14A
Dimmable control box 1-10V, 24/48V. For remote installation.



OPTIONAL
Accessory
Installation
60.3014.11
Suspension rod with 1m rose. M6 thread



OPTIONAL
Accessory
Installation
60.3097.11
1 m suspension rod with ceiling rose with m6 thread



OPTIONAL
Accessory

08.8883.40A


Canopy surface White, Power
Supply not included order
separately



OPTIONAL
Corner

06.1657.40

90° Corner



OPTIONAL
Power supply

Electrical

08U0002.30A1V

Surface mount canopy 1/10V
Dimmable




OPTIONAL

Electrical

306-000369

Recessed power supply rose



OPTIONAL
Power supply

Electrical

08U0002.30

Surface mount canopy Non
Dimmable