

06.1629.40.90 White

## The Running Magnet Suspension Down Feed Unit Profile

Designed by FLOS Architectural



Length: 98.42 - Suspension

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

Mounting	Suspension
Power (W)	100

### Physical

Color	White
Length (in)	98.42
Net weight (lb)	15.44
Package volume (in)	4455
IP internal	20



### Download

Family spec sheet	ZIP
Mounting instructions	PDF



### Electrical

Insulation class	II
Forward voltage (V)	24
Driver	Remote

Accessories & Power Supply



REQUIRED  
Power supply  
Electrical


LEDSB60W24V-NDM-D01  
LED Driver, 24VDC, 60W, Non-Dimming, 120-277V



REQUIRED  
Power supply  
LEDSB96W24V-NDM-D01  
LED Driver, 24VDC, 96W, Non-Dimming, 120-277V



REQUIRED  
Power supply  
Electrical  
LEDSB30W24V-NDM-D01  
LED Driver, 24VDC, 30W, Non-Dimming, 120-277V




REQUIRED  
Electrical  
08.8886.40  
Surface power supply for direct and indirect lighting with housing for the driver



REQUIRED  
Installation  
08.8887.40A

Endcap. 2 unit kit




OPTIONAL  
Power supply  
Electrical  
08.0613.14A  
Dimmable control box 1-10V, 24/48V. For remote installation.



OPTIONAL  
Accessory  
Installation  
60.3014.11  
Suspension rod with 1m rose. M6 thread



OPTIONAL  
Accessory  
Installation  
60.3097.11  
1 m suspension rod with ceiling rose with m6 thread



OPTIONAL  
Accessory

08.8883.40A


Canopy surface White, Power  
Supply not included order  
separately



OPTIONAL  
Corner

06.1657.40

90° Corner



OPTIONAL  
Power supply

Electrical

08U0002.30A1V

Surface mount canopy 1/10V  
Dimmable




OPTIONAL

Electrical

306-000369

Recessed power supply rose



OPTIONAL  
Power supply

Electrical

08U0002.30

Surface mount canopy Non  
Dimmable