



06.1616.14A90 Black

# The Running Magnet Suspension Up&Down Feed Unit Profile

Designed by FLOS Architectural



Length: 78.74 - Suspension

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

## Main specifications

Mounting	Suspension
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Power (W)	100
System flux (lm)	1688

## Physical

Color	Black
Orientation	Fixed
Length (in)	78.74
Net weight (lb)	12.79
Package volume (in)	3601
IP internal	20



Down	load
	ıouu

Family spec sheet	<u>↓</u> ZIP
Mounting instructions	.↓. PDF

## Photometric Files

LDT / IES















# Schematic light drawing



Luminous flux **l**uminaire 1688 lm

Angle:	91°
E(lx)	D(m)
728	2.05
182	4.10
81	6.15
45	8.20
29	10.25
	E(lx) 728 182 81 45

https://professional.flos.com/en-US/us/product/the-running-magnet-suspension-updown-feed-unit-profile-06.1616.14a90/

06.1616.14A90

## Photometric

Lighting type	Indirect
Light distribution	Symmetric
CCT (K)	3000
Beam angle CO-180 (°)	91
UGR <sub>L</sub>	<10

## Electrical

Insulation class	II
Forward voltage (V)	24
Driver	Remote

https://professional.flos.com/en-US/us/product/the-running-magnet-suspension-updown-feed-unit-profile-06.1616.14a90/

## **Accessories & Power Supply**



REQUIRED Installation

08.8887.14A

Endcap. 2 unit kit



OPTIONAL Accessory

08.8883.14A

Canopy surface Black, Power Supply not included order separately