


06.5013.40 White

The Tracking Magnet Surface/Suspension Profile Casambi / Dali / 1-10V compatible

Designed by FLOS Architectural, 2017



Electromechanical profile for surface-mounting, available in lengths from 1m to 3m.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Suspension, Ceiling surface
Environments	Indoor dry location
Light sources included	no

Physical

Color	White
Trim	No
Field cuttable	Yes
Length (in)	98.42
Net weight (lb)	6.70
IP internal	20
IP external	20



Download

Family spec sheet	ZIP
Mounting instructions	ZIP



Electrical

Forward voltage (V)	48
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable
Emergency type	No

Notes

Version compatible with "On board dimmer" luminaries and version compatible with system controlled luminaries (DALI, 1-10V, FLOS SMART CONTROL) available. Corners, connectors and accessories common for the two profile versions. Feed connector, intermediated connector, end-caps and attachment accessories to be ordered separately. Mechanical 90° corners available in the same plane (symmetrical element for left and right corner) and 90° symmetrical internal corners in a different plane. Intermediate connectors to be ordered separately if electrical continuity on corners is required. Corners do not admit installation of spots.

Accessories & Power Supply



REQUIRED
Power supply

LEDSB60W48V-NDM-U01

LED Driver, 48VDC, 60W, Non-Dimming, 120-277V

REQUIRED
Power supply

LEDSB60W48V-NDM-D01

LED Driver, 48VDC, 60W, Non-Dimming, 120-277V

REQUIRED
Power supply

Electrical

LEDSB30W48V-NDM-D01

LED power supply source for remote installation, 48V/30W

REQUIRED
Power supply

LEDSB40W48V-NDM-U01

LED Driver, 48VDC, 40W, Non-Dimming, 120-277V



REQUIRED
Power supply

LEDSB96W48V-NDM-D01

LED Driver, 48VDC, 96W, Non-Dimming, 120-277V

REQUIRED
Power supply

Electrical

08.0613.14A

Dimmable control box 1-10V, 24/48V. For remote installation.

REQUIRED
Accessory

Electrical

08.0611.14

The Tracking Magnet Profile Feed Connector

REQUIRED
Accessory

Electrical

08.0612.14

The Tracking Magnet Profile Intermediate Connector Straight




REQUIRED
Accessory

Electrical

08.0614.14

The Tracking Magnet Profile
Intermediate Connector
Flexible/Electrical Corner



REQUIRED
Accessory

Installation

08.0615.00

Ceiling fixing kit



REQUIRED
Accessory

Installation

08.8634.00

4m suspension steel cable



REQUIRED
Accessory

Installation

60.3014.11

Suspension rod with 1m rose.
M6 thread



REQUIRED
Accessory

Installation

60.3014.14

1 m suspension rod with ceiling
rose kit. M6 thread



REQUIRED
Accessory

Installation

60.3097.11

1 m suspension rod with ceiling
rose with m6 thread



REQUIRED
Accessory

Installation

60.3097.14

1 m suspension rod extension
set with m6 thread



REQUIRED
Accessory

06.5017.40

The Tracking Magnet
Surface/Suspension Profile End
Caps



REQUIRED
Power supply

LEDSB96W48V-NDM-U01


LED Driver, 48VDC, 96W, Non-Dimming, 120-277V



REQUIRED
Accessory

08.8883.40A


Canopy surface White, Power Supply not included order separately



REQUIRED
Accessory

08.8883.14A

Canopy surface Black, Power Supply not included order separately




REQUIRED
Accessory

Installation

08.0616.00


Ceiling fixing kit



OPTIONAL
Corner

06.5005.14


The Tracking Magnet Recessed Profile 90° Mechanical Corner



OPTIONAL
Corner

06.5006.14

The Tracking Magnet Recessed Profile Inner Mechanical Corner



OPTIONAL
Corner

06.5007.14


The Tracking Magnet Recessed Profile Outer Mechanical Corner



OPTIONAL
Installation

08.8866.14

Fixed ceiling kit. 2 unit kit



OPTIONAL
Bracket

08.8867.14UL

Track Ceiling Mounting clip 1/4"
Kit - 1 Units