

FLOS

09.0120.30B White

Thin LED 1201 mm


Designed by FLOS Architectural, 2015



Wall application luminaire for indirect lighting with LED. Remote transformer not included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall surface
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	23.9
Source flux (lm)	2450
Lumen Output (lm)	2173

Physical

Colour	White
Trim	No
Orientation	Fixed
Length (mm)	1201
Net weight (kg)	0.9
IP internal	20
IP external	20

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  ZIP

Technical Drawings


2D  ZIP

3D  ZIP

 Bim  ZIP



Schematic light drawing



Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	101
Beam angle C90-270 (°)	43
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	No
Power supply type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1
Emergency	No

Notes

55 LEDs

Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.9089
Electronic transformer with
constant voltage (24V) for LED.
100/240V. 60W



REQUIRED
Power supply
Electrical

60.9681
Remote power supply. Dimmable
through 0-1/10V.protocol. 24V.
Dimming range 10-100%



REQUIRED
Power supply
Electrical

60.9683
Remote power supply. Dimmable
through Casambi protocol. 24V.
Dimming range 10-100%



REQUIRED
Power supply
Electrical

60.9880
Remote power supply. Dimmable
through DALI protocol. 24V.
Dimming range 10-100%.
Minimum load 20W



REQUIRED
Power supply
Electrical

60.9881
Mains Dimming, 24Vdc
continuous voltage power supply
60W, 220/240V - 50/60Hz