

# FLOS

09.0101.30B White

## Thin LED 2040 mm


Designed by FLOS Architectural, 2015



Wall application luminaire for indirect lighting with LED. Remote transformer not included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Wall surface        |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 41                  |
| Source flux (lm)       | 4266                |
| Lumen Output (lm)      | 3726                |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | White |
| Trim            | No    |
| Orientation     | Fixed |
| Length (mm)     | 2040  |
| Net weight (kg) | 0.9   |
| IP internal     | 20    |
| IP external     | 20    |

### Download

Mounting instructions  PDF

### Photometric Files

LDT / IES  ZIP

### Technical Drawings


2D  ZIP

3D  ZIP

 Bim  ZIP



Schematic light drawing



Photometric

|                        |            |
|------------------------|------------|
| Lighting type          | Indirect   |
| Light distribution     | Asymmetric |
| CCT (K)                | 3000       |
| CRI>                   | 90         |
| Beam angle C0-180 (°)  | 101        |
| Beam angle C90-270 (°) | 43         |
| UGR <sub>L</sub>       | <10        |

Electrical

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| Insulation class    | III                                                 |
| Forward voltage (V) | 24                                                  |
| Power supply        | Remote excluded                                     |
| Dimmable            | No                                                  |
| Power supply type   | Non Dimmable,<br>Dimmable 1-10V,<br>Dimmable DALI 1 |
| Emergency           | No                                                  |

Notes

84 LEDs

Accessories & Power Supply



REQUIRED  
Power supply  
Electrical

60.9089  
Electronic transformer with  
constant voltage (24V) for LED.  
100/240V. 60W



REQUIRED  
Power supply  
Electrical

60.9681  
Remote power supply. Dimmable  
through 0-1/10V.protocol. 24V.  
Dimming range 10-100%



REQUIRED  
Power supply  
Electrical

60.9683  
Remote power supply. Dimmable  
through Casambi protocol. 24V.  
Dimming range 10-100%



REQUIRED  
Power supply  
Electrical

60.9880  
Remote power supply. Dimmable  
through DALI protocol. 24V.  
Dimming range 10-100%.  
Minimum load 20W



REQUIRED  
Power supply  
Electrical

60.9881  
Mains Dimming, 24Vdc  
continuous voltage power supply  
60W, 220/240V - 50/60Hz