

FLOS


60.3105.14.US Black

Three Phase Track Recessed 8ft



Length: 8 - Wall recessed, Ceiling recessed

To be mounted with the surface track inside, not included, needs to be ordered separately. GLOBAL TRACK offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL TRACK lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of the three-circuit system are its high loading capacity and the possibility of forming independent fixture groups in all three circuits. This permits illumination of the most demanding environments. To be fixed with specific screw plugs that come with the track. All accessories need to be order separately.



How to order sample

SURFACE TRACK	60.310X	.XX	x QTY 1
	Part number	Finish	
+ RECESSED HOUSING	60.311X	.XX	x QTY 1
	Part number	Finish	

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

[Download](#)

Family spec sheet



Main specifications

Mounting Wall recessed, Ceiling recessed

Environments Indoor dry location

Physical

Color Black

Trim Yes

Field cuttable Yes

Length (in) 8



Electrical

Dimmable No

Accessories & Power Supply



OPTIONAL
Accessory

Installation

60.3016.11.US

Blind end



OPTIONAL
Accessory

Installation

60.3016.14.US

Blind end



OPTIONAL
Accessory

Installation

60.3025.11.US

Bracket



OPTIONAL
Accessory

Installation

60.3025.14.US

Bracket



OPTIONAL
Accessory

Mounting

60.3054.00.US

Lead bending key



OPTIONAL
Accessory

Electrical

60.3038.11.US

Live End Feed Right XTS 12



OPTIONAL
Accessory

Electrical

60.3038.14.US

Live End Feed Right XTS 12



OPTIONAL
Accessory

Electrical

60.3039.11.US

Live end left



OPTIONAL
Accessory

Electrical

60.3039.14.US

Live end left

Spare Parts



.	Blind end	60.3016.11.US
.	Blind end	60.3016.14.US
.	Cross Coupling	60.3036.11.US
.	Cross Coupling	60.3036.14.US
.	Live center Feed	60.3043.11.US
.	Live center Feed	60.3043.14.US
.	Straight connector	60.3044.11.US
.	Straight connector	60.3044.14.US
.	Corner adjustable connector	60.3046.11.US
.	Corner adjustable connector	60.3046.14.US
.	Connector 90° Inside	60.3029.11.US
.	Connector 90° Inside	60.3029.14.US
.	Connector T - Inside Left	60.3048.11.US
.	Connector T - Inside Left	60.3048.14.US



Accessory

Installation

60.3016.11.US

Blind end



Accessory

Installation

60.3016.14.US

Blind end



Accessory

Electrical

60.3036.11.US

Cross Coupling



Accessory

Electrical

60.3036.14.US

Cross Coupling



Accessory

Electrical

60.3043.11.US

Live center Feed



Accessory

Electrical

60.3043.14.US

Live center Feed



Accessory

Electrical

60.3044.11.US

Straight connector



Accessory

Electrical

60.3044.14.US

Straight connector



Accessory

Electrical

60.3046.11.US

Corner adjustable connector

Accessory

Electrical

60.3046.14.US

Corner adjustable connector

Accessory

Electrical

60.3029.11.US

Connector 90° Inside

Accessory

Electrical

60.3029.14.US

Connector 90° Inside



Accessory

Installation

60.3048.11.US

Connector T - Inside Left

Accessory

Installation

60.3048.14.US

Connector T - Inside Left