

# FLOS


60.3101.14.US Black

## Three Phase Track Surface/Pendant 4ft

Length: 4 - Suspension, Ceiling surface



GLOBAL TRACK offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL TRACK lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of the three-circuit system are its high loading capacity and the possibility of forming independent fixture groups in all three circuits. This permits illumination of the most demanding environments. To be fixed with specific screw plugs that come with the track. All accessories need to be order separately.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Download

Family spec sheet



### Main specifications

Mounting	Suspension, Ceiling surface
Environments	Indoor dry location

### Physical

Color	Black
Field cuttable	Yes
Length (in)	4



### Electrical

Dimmable No

## Accessories & Power Supply



OPTIONAL  
Accessory

Installation

60.3016.11.US

Blind end



OPTIONAL  
Accessory

Installation

60.3016.14.US

Blind end



OPTIONAL  
Accessory

Installation

60.3025.11.US

Bracket



OPTIONAL  
Accessory

Installation

60.3025.14.US

Bracket



OPTIONAL  
Accessory

Mounting

60.3054.00.US

Lead bending key



OPTIONAL  
Accessory

Electrical

60.3038.11.US

Live End Feed Right XTS 12



OPTIONAL  
Accessory

Electrical

60.3038.14.US

Live End Feed Right XTS 12



OPTIONAL  
Accessory

Electrical

60.3039.11.US

Live end left



OPTIONAL  
Accessory

Electrical

60.3039.14.US

Live end left

## Spare Parts



.	Blind end	60.3016.11.US
.	Blind end	60.3016.14.US
.	Cross Coupling	60.3036.11.US
.	Cross Coupling	60.3036.14.US
.	Live center Feed	60.3043.11.US
.	Live center Feed	60.3043.14.US
.	Straight connector	60.3044.11.US
.	Straight connector	60.3044.14.US
.	Corner adjustable connector	60.3046.11.US
.	Corner adjustable connector	60.3046.14.US
.	Connector 90° Inside	60.3029.11.US
.	Connector 90° Inside	60.3029.14.US
.	Connector T - Inside Left	60.3048.11.US
.	Connector T - Inside Left	60.3048.14.US



Accessory

Installation

60.3016.11.US

Blind end



Accessory

Installation

60.3016.14.US

Blind end



Accessory

Electrical

60.3036.11.US

Cross Coupling



Accessory

Electrical

60.3036.14.US

Cross Coupling



Accessory

Electrical

60.3043.11.US

Live center Feed



Accessory

Electrical

60.3043.14.US

Live center Feed



Accessory

Electrical

60.3044.11.US

Straight connector



Accessory

Electrical

60.3044.14.US

Straight connector



Accessory

Electrical

60.3046.11.US

Corner adjustable connector

Accessory

Electrical

60.3046.14.US

Corner adjustable connector

Accessory

Electrical

60.3029.11.US

Connector 90° Inside

Accessory

Electrical

60.3029.14.US

Connector 90° Inside



Accessory

Installation

60.3048.11.US

Connector T - Inside Left

Accessory

Installation

60.3048.14.US

Connector T - Inside Left