

# FLOS

09.4517.30A9S White

## UT Downlight Trim Ø 57


Designed by FLOS Architectural, 2017



The UT Spot is a family of high output indoor lights suitable for any application, from museum exhibitions to commercial premises and offices or residential environments. Remodel type IC rated employing remote drivers, for indoor use to be mounted on ceilings & displays, available in LED sources with choice of lumens, color temperature or beam in ELV& FF or 1-10V dimming versions. The UT Spot Downlight version can operate as downlight (up position) or as adjustable spotlight (down position). The optical housing of the product is in high-pressure injected aluminum, with white or black finishes.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Number of lamps        | 1                   |
| Power (W)              | 18                  |
| Source flux (lm)       | 1879.26             |
| System flux (lm)       | 918                 |

### Physical

|                          |            |
|--------------------------|------------|
| Color                    | White      |
| Trim                     | Yes        |
| Orientation              | Adjustable |
| Rotation (°)             | 360        |
| Longitudinal tilting (°) | 90         |
| Net weight (lb)          | 1.62       |
| Package volume (in)      | 428        |
| IP internal              | 20         |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files


|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 4000      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 21        |
| Beam angle C90-270 (°) | 21        |
| UGR <sub>L</sub>       | <10       |

Electrical

|                     |        |
|---------------------|--------|
| Insulation class    | III    |
| Forward voltage (V) | 36     |
| LED current (mA)    | 450    |
| Driver              | Remote |

Notes


Integral LED is not field replaceable. IC-rated downlight for direct insulation contact. Fixture is constant Current Low Volatge LED, Class 2. Just 1 accessory can be install at the time. For filter options contact Flos. 3500K available, but not cataloged. Consult factory for additional color temperatures.

Accessories & Power Supply



REQUIRED  
Power supply  
Electrical

SP25W450MA-10V-A02  
Splice Box UL 7"x3-5/8"x1-1/4"  
450mA 25W 0-10V



REQUIRED  
Power supply  
Electrical

SP40W450MA-10V-A02  
Splice Box UL 7"x3-5/8"x1-1/4"  
450mA 40W 0-10V




OPTIONAL  
Accessory  
Optical

08.0526.00  
Snoot shielding cone



OPTIONAL  
Accessory  
Optical

08.8428.00  
Honeycomb



OPTIONAL  
Accessory  
Optical

08.8429.00  
Screening crosspiece



OPTIONAL  
Accessory  
Optical

08.8431.00  
Elliptical lens




OPTIONAL  
Accessory  
Optical

08.8432.00  
Flood lens



OPTIONAL  
Accessory  
Optical

08.0526.40  
Snoot shielding cone



## OPTIONAL Housing and Hanger Bar

TRAY-0017

Registration Tray - non electrical,  
place holder for non IC new  
construction, UT57 Trim Ø3.56"