



UT Downlight Trim Ø 86 Dali Version

Designed by FLOS Architectural, 2017



Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed	
Environments	Indoor dry location	
Light source type	LED	
Light sources included	Yes	
LED type	LED array	
Lamp category	LED	
Number of lamps	1	
System power (W)	27	
Source flux (lm)	3375	
Lumen Output (lm)	2053	
Efficacy (Im/W)	76.04	

Physical

Colour	White
Trim	Yes
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Recessed depth (mm)	176
Spot diameter (mm)	86
Net weight (kg)	0.74
IP internal	20



Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	⊥ ZI	ΙP
3D	↓ Z	ΙP









https://professional.flos.com/en/global/product/ut-downlight-trim-86-dali-version-09.4912.30bda/

09.4912.30BDA

Schematic light drawing



Bean	Beam Angle:	
h(m)	E(lx)	D(m)
1	5741	0.67
2	1435	1.34
3	638	2.01
4	359	2.69
5	230	3.36

Luminous flux luminaire 2053 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	37
Beam angle C90-270 (°)	37
UGR _L	<10

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **G**



Replaceable (LED only)
light source by a
professional



Replaceable control gear by a professional

Notes

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

Accessories & Power Supply









OPTIONAL Accessory

Optical

08.8163.68

Elliptical lens

OPTIONAL Accessory

Optical

08.8175.68

Flood lens

OPTIONAL Accessory

Optical

08.8410.00

Holding ring

OPTIONAL Accessory

Optical

08.8411.0

Screening crosspiece



OPTIONAL Accessory

Optical

08 8495 14

Honeycomb