



09.4463.14ADA Black

UT Spot Ceiling Ø 57 Dali Version


Designed by FLOS Architectural, 2017



Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light Source Type	LED
LED type	LED array
Lamp category	LED
Ilcos	No
Bulb finish	Clear
Number of heads	1
Power (W)	23.2
System power (W)	23.2
Source flux (lm)	1985.71
System flux (lm)	997

Physical

Colour	BIACK
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	57
Net weight (kg)	0.59
IP internal	20
IP external	20

Download

Mounting instructions	$\overline{\gamma}$	PDF
Mounting instructions	.4.	PDF

Photometric Files

LDT / IES



Technical Drawings

2D	<u>↓</u> ZIP
3D	⊥ ZIP
a Bim	<u>↓</u> ZIP















https://professional.flos.com/en/global/product/ut-spot-ceiling-57-dali-version-09.4463.14ada/

09.4463.14ADA

Schematic light drawing



Beam Angle:		10°
h(r	n) E(lx)	D(m)
1	11643	0.18
2	2911	0.36
3	1294	0.54
4	728	0.72
5	466	0.90

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	10
Beam angle C90-270 (°)	10

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240V
Alternating current voltage (Vac)	230
LED current (mA)	550
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency type	No

Notes

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory.

Accessories & Power Supply









OPTIONAL Accessory

Optical

08.0526.00

Snoot shielding cone

OPTIONAL Accessory

Optical

08.8428.00

Honeycomb

OPTIONAL Accessory

Optical

na a429 no

Screening crosspiece

OPTIONAL Accessory

Optical

08.8431.0

Elliptical lens







OPTIONAL Accessory

Optical

08 8432 00

Flood lens

OPTIONAL Accessory

Optical

08 0526 40

Snoot shielding cone

OPTIONAL Accessory

Optical

18 0526 BW

Snoot shielding cone