



UT Spot Track Ø 86 Dali Version

Designed by FLOS Architectural, 2017



Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	32.8
System power (W)	32.8
Source flux (lm)	3959
Lumen Output (lm)	2650

Physical

Colour	White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	86
Net weight (kg)	0.74
IP internal	20
IP external	20



Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

<u>↓</u> ZIP

Technical Drawings

2D	<u>↓</u> ZIP
3D	<u>↓</u> ZIP
₿Bim	⊥ ZIP









https://professional.flos.com/en/global/product/ut-spot-track-86-dali-version-09.4840.30bda/

09.4840.30BDA

Schematic light drawing



Ве	am	Angle:	12°
h(r	n)	E(lx)	D(m)
1	3	4142	0.21
2		8535	0.41
3		3794	0.62
4		2134	0.82
5		1366	1.03

Be	am	Angle:	12
h(r	n)	E(lx)	D(n
1	3	4142	0.2
2		8535	0.4
3		3794	0.6
4		2134	0.8
_			4.0

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	12
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	II	
Frequency (Hz)	50/60	
Main voltage (Vac)	220-240	
LED current (mA)	900	
Power supply	Integrated	
Dimmable	Yes	
Power supply type	Dimmable DALI 1	
Dimming interface	Remote Dimmable (Dimmer Not Included)	

Notes

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.

Accessories & Power Supply









OPTIONAL Accessory

Optical

08.8163.68

Elliptical lens

OPTIONAL Accessory

Optical

08.8175.68

Flood lens

OPTIONAL Accessory

Optical

08.8410.00

Holding ring

OPTIONAL Accessory

Optical

08.8411.0

Screening crosspiece



OPTIONAL Accessory

Optical

08 8495 14

Honeycomb