



UT Spot Track Ø 86 GA


Designed by FLOS Architectural, 2015



Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated. .30 versions come with the track adapter, the arm and the rear of the head in black.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track	
Environments	Indoor dry location	
Light Source Type	LED	
LED type	ype Phosphor LED	
Lamp category	LED	
Ilcos	No	
Bulb finish	Clear	
Number of heads	1	
Power (W)	23	
System power (W)	27.5	
Source flux (lm)	2883	
System flux (lm)	2134	

Physical

Colour	White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	86
Net weight (kg)	0.75
IP internal	20
IP external	20

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	⊥ ZIP
3D	⊥ ZIP
⋒ Bim	.↓. ZIP















https://professional.flos.com/en/global/product/ut-spot-track-86-ga-09.7731.30a/

09.7731.30A

Schematic light drawing



Beam Angle:		23°
h(n	n) E(lx)	D(m)
1_	10058	0.41
2	2514	0.81
3	1118	1.22
4	629	1.63
5	402	2.03

Luminous flux luminaire 2134 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	23
Beam angle C90-270 (°)	23

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240V
Alternating current voltage (Vac)	230
LED current (mA)	900
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Dimming interface	Not Dimmable
Emergency type	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

Accessories & Power Supply



OPTIONAL Accessory

Optical

08.8411.00

Screening crosspiece