



03.6170.14 Black

Wan Spot

Designed by Johanna Grawunder, 2013



Halogen - 40W - Beam° 68

Spotlight to be installed recessed on ceiling/wall with main voltage source

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Celling Surface
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
Lamp category	Halogen
Lamp type	QT-14
Lamp holders	G9
Number of lamps	1
Power (W)	40

Physical

Trim No Orientation Adjustable Rotation (°) 360 Recessed depth (mm) 50 Net weight (kg) 0.50	Colour	BIack
Rotation (°) 360 Recessed depth (mm) 50	Trim	No
Recessed depth (mm) 50	Orientation	Adjustable
	Rotation (°)	360
Net weight (kg) 0.50	Recessed depth (mm)	50
	Net weight (kg)	0.50
IP internal 20	IP internal	20
IP external 20	IP external	20



Download

Mounting instructions



















Photometric

Lighting type	Direct
Light distribution	Symmetric
Beam angle C0-180 (°)	68
Beam angle C90-270 (°)	68
Extreme cut off	No
UGR _L	<19

Electrical

Insulation class	II
Frequency (Hz)	50/60
Dimmable	No
Emergency	No