

FLOS



F9513009 Grey Cable/White Ring

Wirering Grey

Designed by Formafantasma, 2018


16W - 712lm - 2700K - CRI> 90



Indirect light wall lighting device with body in calendered, extruded aluminium with galvanised or varnished finish. The special tangent cable, in coloured rubber, provides the power. The cable is fixed to the wall with ABS joints in the same finish as the ring. Dimming via switch pedal on the cable. Power supply on adapter with interchangeable plugs. Useful cable length is 2.5 metres.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Wall
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	16
System flux (lm)	712

Physical

Colour	Grey Cable/White Ring
Length (mm)	310
Cord length (mm)	2500
Net weight (kg)	0.94
Package volume (m3)	0.02
IP internal	20

Download

[Mounting instructions](#) PDF

[Spare Parts](#) PDF

Photometric Files

[LDT / IES](#) LDT


Technical Drawings

[2D](#) ZIP

[3D](#) ZIP



Schematic light drawing



Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 24V
Dimming interface	Dimmer Integrated
Plug type	Type G, Type A, Type C
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F




Replaceable (LED only)
light source by a
professional



Replaceable control
gear by an end-user

Spare Parts



- | | | |
|-----|--|-----------|
| 01. | Kit with screws, nuts and components | RF9510100 |
| 02. | Ring assembly | RF26674 |
| 03. | Electrical mounting body assembly | RF26649 |
| 04. | Electrical mounting assembly with dimmer | RF26645 |
| 05. | Black plug assembly kit & 24V driver | RF3320100 |

DOWNLOAD



RF9510100
Kit with screws, nuts and components



RF26674
Ring assembly



RF26649
Electrical mounting body assembly



RF26645
Electrical mounting assembly with dimmer



RF3320100
Black plug assembly kit & 24V driver