



Workmates Suspension Up&Down High Efficiency

Designed by FLOS Architectural, 2023




LED - Top LED - 53W - 5570lm - 3000K - CRI> 90 - Beam° 73

Suspension luminaire. Up&Down emission. High-efficiency light source. Driver not included (accessory kit for remote or surface driver). For Non Dimming models, you can configure the Up&Down luminous flux in 70/30 and 40/60 ratios (select the accessory kit for the driver concerned). Adjustable suspension height. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m2 @ 65°<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT




Main specifications

| Mounting | Suspension Indoor dry location | |
|------------------------|--------------------------------|--|
| Environments | | |
| Light source type | LED | |
| Light sources included | Yes | |
| LED type | Top LED | |
| Lamp category | LED | |
| Number of lamps | 1 | |
| Power (W) | 53 | |
| System power (W) | 57 | |
| Source flux (lm) | 6471 | |
| Lumen Output (lm) | 5570 | |

Physical

| Colour | All White |
|------------------|-----------|
| Cord colour | White |
| Cord length (mm) | 5000 |
| Net weight (kg) | 2.18 |
| IP internal | 20 |

















https://professional.flos.com/en/global/product/workmates-suspension-updown-high-efficiency-05.6340.40.78/

05.6340.40.78

Schematic light drawing



| Bear | n Angle: | - 75 |
|------|----------|------|
| h(m) | E(lx) | D(m |
| 1 | 1406 | 1.4 |
| 2 | 351 | 2.9 |
| 3 | 156 | 4.4: |
| 4 | 88 | 5.9 |

56

5

7.39

Photometric

| Lighting type | Total |
|--------------------------|-----------------------|
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| Rf fidelity index | 89 |
| Rg gamut index | 103 |
| LED Life / Failure Ratio | L80B50>60.000h_Tc85°C |
| Beam angle C0-180 (°) | 73 |
| Beam angle C90-270 (°) | 74 |
| Extreme cut off | Yes |
| UGR _L | <16 |

Electrical

| Forward voltage (V) | 48 | |
|---------------------|----------------------------------|--|
| LED current (mA) | 700 | |
| Power supply | Remote | |
| Dimmable | Yes | |
| Power supply type | Non Dimmable, Dimmable DALI 2 | |
| Batteries inside | No | |

Accessories & Power Supply



REQUIRED Power supply

Installation

08.0901.AP

Remote Power Supply Kit for Workmates Suspension Up&Down - Non dimmable



REQUIRED
Power supply

Installation

08.0901.14

Remote Power Supply Kit for Workmates Suspension Up&Down - Non dimmable



REQUIRED Power supply

Installation

08.0901.40

Remote Power Supply Kit for Workmates Suspension Up&Down - Non dimmable



REQUIRED
Power supply

Installation

08.0904.AP

Remote Power Supply Kit for Workmates Suspension Up&Down - Dimmable Dali



REQUIRED Power supply

Installation

08.0904.14

Remote Power Supply Kit for Workmates Suspension Up&Down - Dimmable Dali



REQUIRED
Power supply

Installation

08.0904.40

Remote Power Supply Kit for Workmates Suspension Up&Down - Dimmable Dali



REQUIRED
Power supply

Electrical

08.0911.AP

Surface Power Supply Kit for Workmates Suspension Up&Down - Non Dimmable



REQUIRED
Power supply

Electrical

8.0911.14

Surface Power Supply Kit for Workmates Suspension Up&Down - Non Dimmable



REQUIRED
Power supply

Electrical

08.0911.40

Surface Power Supply Kit for Workmates Suspension Up&Down - Non Dimmable



REQUIRED
Power supply

Electrical

08.0914.AF

Surface Power Supply Kit for Workmates Suspension Up&Down - Dimmable Dali



REQUIRED Power supply

Electrical

08.0914.14

Surface Power Supply Kit for Workmates Suspension Up&Down - Dimmable Dali



REQUIRED Power supply

Electrical

08.0914.40

Surface Power Supply Kit for Workmates Suspension Up&Down - Dimmable Dali



REQUIRED Power supply

08.0921.AP

Recessed Power Supply Kit for Workmates Suspension Up&Down - Non Dimmable



REQUIRED
Power supply

08.0921.14

Recessed Power Supply Kit for Workmates Suspension Up&Down - Non Dimmable



REQUIRED
Power supply

08.0921.40

Recessed Power Supply Kit for Workmates Suspension Up&Down - Non Dimmable



REQUIRED
Power supply

08.0924.AP

Recessed Power Supply Kit for Workmates Suspension Up&Down - Dimmable Dali



REQUIRED Power supply

08 0924 14

Recessed Power Supply Kit for Workmates Suspension Up&Down - Dimmable Dali



REQUIRED
Power supply

08.0924.40

Recessed Power Supply Kit for Workmates Suspension Up&Down - Dimmable Dali