

FLOS

05.6347.14.CB Black

Workmates Suspension Up&Down High Efficiency

Designed by FLOS Architectural, 2023




LED - Top LED - 58.5W - 5181lm - 4000K - CRI> 90 - Beam° 71

Suspension luminaire. Up&Down emission. High-efficiency light source. Driver not included (accessory kit for remote or surface driver). For Non Dimming models, you can configure the Up&Down luminous flux in 70/30 and 40/60 ratios (select the accessory kit for the driver concerned). Adjustable suspension height. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m2 @ 65°<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	58.5
System power (W)	61
Source flux (lm)	6833
Lumen Output (lm)	5181

Physical

Colour	Black
Cord colour	Black
Cord length (mm)	5000
Net weight (kg)	2.09
IP internal	20

Download

Mounting instructions  PDF


Photometric Files

LDT / IES  ZIP

Technical Drawings


2D  ZIP

3D  ZIP



Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional

<https://professional.flos.com/en/global/product/workmates-suspension-updown-high-efficiency-05.6347.14.cb/>


05.6347.14.CB

©2022 Flos - P.IVA 00290820174 - 11/21/2025

professional.flos.com | info@flos.com 1/4

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Photometric

Lighting type	Total
Light distribution	Asymmetric
CCT (K)	4000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	98
LED Life / Failure Ratio	L80B50>60.000h_Tc85°C
Beam angle C0-180 (°)	71
Beam angle C90-270 (°)	81
Extreme cut off	Yes
UGR _L	<16

Electrical

Forward voltage (V)	48
LED current (mA)	700
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmable Casambi
Batteries inside	No

Accessories & Power Supply



REQUIRED
Power supply
Installation

08.0906.AP
Remote Power Supply Kit for
Workmates Suspension -
Dimmable Casambi



REQUIRED
Power supply
Installation

08.0906.14
Remote Power Supply Kit for
Workmates Suspension -
Dimmable Casambi



REQUIRED
Power supply
Installation

08.0906.40
Remote Power Supply Kit for
Workmates Suspension -
Dimmable Casambi



REQUIRED
Power supply
Electrical

08.0915.AP
Surface Power Supply Kit for
Workmates Suspension
Up&Down Tunable White -
Casambi & Dimmable Dali



REQUIRED
Power supply
Electrical

08.0915.14
Surface Power Supply Kit for
Workmates Suspension
Up&Down Tunable White -
Casambi & Dimmable Dali




REQUIRED
Power supply
Electrical

08.0915.40
Surface Power Supply Kit for
Workmates Suspension
Up&Down Tunable White -
Casambi & Dimmable Dali



REQUIRED
Power supply

08.0925.AP
Recessed Power Supply Kit for
Workmates Suspension
Up&Down Tunable White -
Casambi & Dimmable Dali



REQUIRED
Power supply

08.0925.14
Recessed Power Supply Kit for
Workmates Suspension
Up&Down Tunable White -
Casambi & Dimmable Dali



REQUIRED Power supply

08.0925.40

Recessed Power Supply Kit for
Workmates Suspension
Up&Down Tunable White -
Casambi & Dimmable Dali