

Workmates Suspension Up&Down Tunable White High Efficiency NEW


Designed by FLOS Architectural, 2023



Suspension luminaire. Up&Down emission, with greater light flux amounts in the upper part. Highefficiency Down light source. Tunable White variable CCT Up light source. Driver not included (accessory kit for remote or surface driver). Adjustable suspension height. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m2 @ 65°<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	47.5
System power (W)	61
Source flux (lm)	7559
System flux (lm)	6500

Physical

Color	All White
Orientation	Fixed
Cord color	White
Net weight (lb)	4.61
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	---------------------

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	3500
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	106
LED Life / Failure Ratio	L80B50>60.000h_Tc85°C
Beam angle C0-180 (°)	73
Beam angle C90-270 (°)	74
Extreme cut off	Yes
UGR _L	<16

Electrical

Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable Casambi
Batteries inside	No

Notes

Class 2 Listed

Accessories & Power Supply



REQUIRED
Accessory

Installation

08.0910.40.9S

SURF.KIT WH WORKM STEEL

WIRE 1C NOPSU UL