

05.5741.40.C6 All White

## Workmates Track Small High Efficiency Casambi

NEW

Designed by FLOS Architectural, 2023




15W - 1855lm - 3500K - CRI> 90 - Beam° 66

Luminaire for use on a three-phase track, with adapters for No Dim, Dali and Casambi (wireless) control. High-efficiency light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to erpendicular). UGR<19. EN12464 - cd/m2 @ 65°<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | yes                 |
| LED type               | Top LED             |
| Number of lamps        | 1                   |
| Power (W)              | 15                  |
| Source flux (lm)       | 2180                |
| Lumen Output (lm)      | 1855                |

### Physical

|                 |           |
|-----------------|-----------|
| Colour          | All White |
| Net weight (kg) | 0.63      |
| IP internal     | 20        |

### Download

Mounting instructions [↓ PDF](#)


### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Direct                |
| Light distribution       | Symmetric             |
| CCT (K)                  | 3500                  |
| CRI>                     | 90                    |
| Rf fidelity index        | 89                    |
| Rg gamut index           | 106                   |
| LED Life / Failure Ratio | L80B50>60.000h_Tc85°C |
| Beam angle C0-180 (°)    | 66                    |
| Beam angle C90-270 (°)   | 65                    |
| Extreme cut off          | No                    |
| UGR <sub>L</sub>         | <16                   |

Electrical

|                    |                                       |
|--------------------|---------------------------------------|
| Insulation class   | II                                    |
| Frequency (Hz)     | 50/60                                 |
| Main voltage (Vac) | 220-240                               |
| LED current (mA)   | 350                                   |
| Power supply       | Integrated                            |
| Dimmable           | Yes                                   |
| Power supply type  | Dimmable Casambi                      |
| Dimming interface  | Remote Dimmable (Dimmer Not Included) |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **G**



Replaceable (LED only) light source by a professional

Replaceable control gear by a professional