


## X Connector Feed Dimmable NEW

Designed by FLOS Architectural, 2023



Ceiling surface, Wall surface

Cross-shaped connector. Can be powered via connections on the back. Rear feeding cable entry.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                               |
|------------------------|-------------------------------|
| Mounting               | Ceiling surface, Wall surface |
| Environments           | Indoor dry location           |
| Light sources included | No                            |

### Physical

|                 |                |
|-----------------|----------------|
| Colour          | Brushed Bronze |
| Net weight (kg) | 0.03           |
| IP internal     | 20             |



### Download

[Mounting instructions](#)

[PDF](#)



### Photometric

|                 |    |
|-----------------|----|
| Extreme cut off | No |
|-----------------|----|

### Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 24                                    |
| Power supply        | Remote excluded                       |
| Dimmable            | Yes                                   |
| Power supply type   | Dimmable                              |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |



Accessories & Power Supply



REQUIRED  
Power supply  
Electrical

60.9352  
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.




REQUIRED  
Power supply  
Electrical

60.9705  
Remote Power Supply Non Dimmable 24V. 60W. 220/240V




REQUIRED  
Power supply  
Electrical

60.9777A  
Remote Power Supply Non Dimmable 24V. 120W. 220/240V




OPTIONAL  
Power supply  
Electrical

08.0613.14A  
Dimmable control box 1-10V, 24/48V. For remote installation.



OPTIONAL  
Component  
Installation

06.2618.40A  
Track Cover 3000mm



OPTIONAL  
Component  
Installation

06.2618.14A  
Track Cover 3000mm



OPTIONAL  
Connector  
Electrical

06.2608.14  
Straight Connector



OPTIONAL  
Connector  
Electrical

06.2608.40  
Straight Connector