



06.2502.18 Deep Brown

Zero Track Surface Profile

Designed by FLOS Architectural, 2018



Electro-mechanical indoor profile for surface installation (ceiling or wall). To be fixed with specific screw plugs that come with the profile.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling surface, Wall surface
Environments	Indoor dry location
Light sources included	no

Physical

Colour	Deep Brown
Trim	No
Length (mm)	3000
Net weight (kg)	0.62
IP internal	20



Download

Mounting instructions















Photometric

Extreme cut off

No

Electrical

Insulation class	III
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable,

https://professional.flos.com/en/global/product/zero-track-surface-profile-06.2502.18/

06.2502.18

Notes

It is necessary to order the power connector, intermediate connectors and covers separately. Feed unit connectors available as 90° flat corner and curve (symmetric element for left/right corner), ceiling/wall - wall/wall inner corner, as well as "T" and "X" shape. For vertical installations, installing the stopper is mandatory. It must be ordered separately.

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.

https://professional.flos.com/en/global/product/zero-track-surface-profile-06.2502.18/

Accessories & Power Supply









REQUIRED Power supply

Electrical

60.9516

Remote Power Supply Non Dimmable 24V. 120W. 220/240V REQUIRED
Power supply

Electrical

06.2510.18A

Power supply surface end. 96W - 220/240V

REQUIRED Power supply

Electrical

06 2511 184

Power supply surface middle. 96W - 220/240V

REQUIRED Power supply

Electrical

60.944

Remote Power Supply Non Dimmable 24V. 100W. 220/240V



REQUIRED
Power supply

Electrical

60.9515

Remote Power Supply Non Dimmable 24V. 60W. 220/240V



REQUIRED
Power supply

Electrical

60.9374

Remote Power Supply Non Dimmable 24V. 60W. 220/240V



REQUIRED
Power supply

Electrical

60.9777A

Remote Power Supply Non Dimmable 24V. 120W. 220/240V



REQUIRED Profile

06.2509.18

Zero Track Surface Profile. End Cap









REQUIRED

06.2540.18

Zero Track Surface Profile. Feed Unit for Remote Power Supply Unit

REQUIRED

06 2541 18

Zero Track Surface Profile. Feed intermediate connector

OPTIONAL Accessory

08.0630.14

Stopper

OPTIONAL Accessory

08.0630.40

Stopper



OPTIONAL

06.2506.14

Zero Track Surface Profile. Intermediate Connector



OPTIONAL

06 2506 40

Zero Track Surface Profile. Intermediate Connector



OPTIONAL Corner

06.2542.18

Zero Track Surface Profile. 90° Flat Corner



OPTIONAL Corner

06.2543.18

Zero Track Surface Profile. Ceiling/wall - wall/wall inner corner







OPTIONAL Corner

06 2544 18

Zero Track Surface Profile. Interior ceiling/ceiling-wall/wall

OPTIONAL Corner

06.2545.18

Zero Track Surface Profile. T-shaped connector

OPTIONAL Corner

06.2546.18

Zero Track Surface Profile. Crossshaped connector