

FLOS

06.2540.14 Black

Zero Track Surface Profile. Feed Unit for Remote Power Supply Unit NEW

Designed by FLOS Architectural, 2020



Feed unit for remote power supply unit. Power cable inserting is possible both from the top and the side.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Surface
Environments	Indoor dry location
Light Source Type	LED
Iicos	No
Bulb finish	Clear

Physical

Colour	Black
Trim	No
Length (mm)	82
Net weight (kg)	0.01
IP internal	20




Download

[Mounting instructions](#)

[PDF](#)

Ecodesign and Energy Labelling



Replaceable control gear by a professional

Electrical

Insulation class	III
Main voltage (Vac)	24
LED voltage Vf (Vdc)	24

Notes

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.

Accessories & Power Supply



REQUIRED
Power supply

Electrical

60.9777

Remote Power Supply Non
Dimmable 24V. 120W. 220/240V

REQUIRED
Power supply

Electrical

60.9359

24V Remote power supply. 25W
110/240V

REQUIRED
Power supply

Electrical

60.9360

24V Remote power supply. 36W-
110V / 45W-240V

REQUIRED
Power supply

Electrical

60.9361

24V Remote power supply. 57W
220/240V



REQUIRED
Power supply

60.9516

Remote Power Supply Non
Dimmable 24V. 120W. 220/240V

REQUIRED
Power supply

Electrical

60.9443

Remote Power Supply Non
Dimmable 24V. 100W. 220/240V

REQUIRED
Power supply

Electrical

60.9515

Remote Power Supply Non
Dimmable 24V. 60W. 220/240V

REQUIRED
Power supply

Electrical

60.9374

Remote Power Supply Non
Dimmable 24V. 60W. 220/240V



OPTIONAL
Accessory

Electrical

60.9394

Controller 0/1-10V or Push Dim.
Max 10A



OPTIONAL
Accessory

Electrical

60.9677

Controller DALI or Push Dim. Max
10A



OPTIONAL
Accessory

Electrical

60.9630

Controller Casambi. Max 10A